

AAKRON XPRESS BOAT TRAILERS detailed SPECIFICATIONS: We reserve the right to change specifications at any time without notice

Check exact current details with our staff when ordering

While the specifications shown here are for our standard products we are happy to customise almost any aspect to suit individual needs.

LARGER TRAILERS:

Model	AX580	AX630	AX630B	AX630BT	AX680	AX680B	AX680BT	AX740	AX740 B	AX740 BT	AX 840 BT	AX 840 EBT
Length over-all m	5.91	6.25	6.25	6.25	7.00	7.00	7.00	7.45	7.45	7.45	8.47	8.47
Main frame width m	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85
Width over-all inc mudguards	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4
Easy entry rear	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Main-frame box section size mm	100x50x3	100x50x3	100x50x3	100x50x3	100x50x3	100x50x3	100x50x3	100x50x4	100x50x4	100x50x4	120x60x4	120x60x4
Drawbar box section mm	100x100x3	100x100x3	100x100x3	100x100x3	100x100x3	100x100x3	100x100x3	100x100x4	100x100x4	100x100x4	100x100x4	100x100x4
Coupler options	std+ braked	std+ braked	BRAKED	BRAKED	std+ braked	BRAKED	BRAKED	std+ braked	BRAKED	BRAKED	BRAKED	BRAKED
Cross frames number	4	4	4	4	4	4	4	5	5	5	6	6
Cross frame box section size	70x50x3	70x50x3	70x50x3	70x50x3	70x50x3	70x50x3	70x50x3	70x50x3	70x50x3	70x50x3	70x50x3	70x50x3
Axles number	1	1	1	2	1	1	2	1	1	2	2	2
Axle type (generally 50x50x5mm)	Gull-wing	Gull-wing	Gull-wing	Gull-wing	Gull-wing	Gull-wing	Gull-wing	Gull-wing	Gull-wing	Gull-wing	Straight 60x60	Straight 60x60
Pads or Wobble rollers	Rollers	Rollers	Rollers	Rollers	Rollers	Rollers	Rollers	Rollers	Rollers	Rollers	Rollers	Rollers
Rear Rollers	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x8	2x8
2 nd from rear rollers	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4
3 rd from rear rollers	2x2	2x2	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4	2x4
4 th from rear rollers								2x2	2x2	2x2	2x2	2x2
5 th from rear rollers (-	-	-	-	-	-				2x2	2x2
Total number of wobble rollers	20	20	24	24	24	24	24	28	28	28	40	40
Entry keel roller	1	1	1	1	1	1	1	1	1	1	1	1
Wheel size	195/50R13C	195/50R13C	195/50R13C	195/50R13C	195/50R13C	195/50R13C	195/50R13C	195/50R13C	195/50R13C	195/50R13C	205/70R14C	205/70R14C
Winch ratio	2 spd to 5:1	3spd to 10:1	3spd to 10:1	3spd to 10:1	3spd to 10:1	3spd to 10:1	3spd to 10:1	3spd to 10:1	3spd to 10:1	3spd to 15:1	3spd to 15:1	3spd to 15:1
Galv. Jockey whl capacity/diameter	500kg/8"	500kg/8"	500kg/8"	500kg/8"	500kg/8"	500kg/8"	500kg/8"	500kg/8"	500kg/8"	500kg/8"	500kg/8"	500kg/8"
Brake option available	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Galv. Spring Leaves	5	6	6	5	6	6	6	6	6	6	8	8
Stainless steel Bearing buddies	Yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Bearings Inner (NZ std) All trailers	L68149/	L68111										
Bearings outer (NZ std) All trailers	L44649/	L44610										
Submersible LED lights all round	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Recommended max payload	1200kg	1200kg	1300	1900	1200	1300	1900	1200	1300	1900	1900	1900